

EliteSeries

Mini Dome Camera

Your Security
Our Solution



Mini Dome Camera

- Progressive Scan CMOS Sensor
- 2M / 3M / 5M Resolution
- Dual Streaming- Full HD 1080P Real Time + D1 Real Time
- Quad Streams Compression- H.264 Baseline / Main / High Profile + MJPEG
- Multi-language Support
- Tampering Alarm
- Wide Dynamic Range

Specifications

Camera			Lens		
Models	BKE-MDM020FFIR-D11		Focal Length	4.0 mm	2.8 mm
Image Sensor	1/2.7" Progressive CMOS		F Number	F 1.5	F 2.0
Effective Pixels	1920(H) x 1080(V)		FOV	78	TBD
Minimum Illumination	0.1 lux (Color)	TBD			
White Balance	Manual / AWB / ATW				
Shutter Speed	1 ~ 1/10000 sec.				
Operation			Network		
Multiple Languages:	English / French / German / Italian / Korean / Simplified Chinese / Traditional Chinese / Russian / Portuguese / Spanish / Japanese		Interface	RJ-45, 10/100Mbps	
Image Setting:	Backlight Compensation	On/Off	Video Compression	H.264 / MJPEG	
	White Balance	Auto / Manual	Video Streaming	Dual Streams 1080p (30 / 25 fps) + D1 (30 / 25 fps) Quad Streams H.264 * 4 / H.264 * 3 + MJPEG	
	Noise Reduction	3D On/Off	Video Resolution	H.264- Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF MJPEG- Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF	
	Wide Dynamic Range	On/Off	Protocol	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF	
	Privacy Mask	On/Off	Security	HTTPS / IP Filter / IEEE 802.1X	
	Brightness	Manual	Event Notification	HTTP / FTP / SMTP	
	Exposure	Auto / Manual	Micro SD	microSDHC 32GB support	
	Sharpness	Manual	Supported Web Browser	Internet Explorer (6.0+) / Chrome / Firefox / Safari	
	Contrast	Manual	User Account	20	
	Saturation	Manual	Password Levels	User and Administrator	
	Hue	Manual			
	Digital Zoom	Support			
	Motion Detection	On / Off			
	Privacy Mask Type	Color			
	Tampering Alarm	On / Off			
Audio	One-way Audio*	Mic in			
	Compression	G.711/G.726			
General			Operating Temperature	-10°C ~ 50°C (14° ~ 122° F)	
			Humidity	10% ~ 90%, No Condensation	
			Weatherproof Standard	Rugged Camera- IP66	
			Dimension	110.2 x 47.7 mm (4.3 x 1.9 in.)	
			Weight	180 g (0.40 lb)	
			Power Source	PoE	
			Power Consumption	3.5 W	
			Regulatory	CE / FCC / RoHS	