

Elite Dome IP Cameras

Day/Night Dome IP Cameras – Vandal Proof Megapixel - H264 Video and Audio



HD



HD MegaPixel Vandal Proof Dome Network Camera – It's all in the Detail

2 MegaPixel Dome POE IP Camera with dual MPEG4 video streams, remote access from Web & 3G mobile phones, 1/3" CMOS sensor, audio + analogue video out presenting a fully featured HD Camera

Overview

The BiKal Elite HD Vandal Proof POE Dome Network Cameras feature High Definition 2 MegaPixel video in a robust yet smart design with flexible features making this one of the most popular Dome MegaPixel cameras on the market today.

Featuring dual audio & video streams, low light performance down to 0.5 Lux with no motion blur in challenging lighting conditions with built in wide angle lens options to suit your surveillance application.

Additional advantages POE power, 2 way audio and alarm/RS485 I/O options. Also includes remote access via Internet browser or 3G mobile phones. Compatible with EyeSoft

Features

- 1/3" CMOS for low light
- 2 MegaPixel 1600 x 1200
- Real Time in 720p HD
- POE (power over Ethernet)
- FREE 64ch Surveillance App
- TI DaVinci DSP Processor
- Dual MPEG4 Video Channels
- 1 to 25/30 fps. (PAL / NTSC)
- Low Light to 0.5 Lux (0.1)
- Day / Night Auto Switch
- 2.8 ~ 11mm Varifocal Lens
- 32k ~ 8Mbps Bandwidth
- Remote Internet Access
- Remote Access on 3G Mobiles
- BNC Analogue Video Out
- Alarm I/O / RS485 I/O
- SD Card Slot / Internal DVR
- Motion Detection
- Tamper Alarm
- Privacy Mask



BIKAL IP CCTV LIMITED

4th Floor, 25 Eccleston Square, London, SW1V 1NS, UK

WEB: www.bikal.co.uk EMAIL: uk@bikal.co.uk Tel: [+44 \(0\)844 804 2400](tel:+44208448042400)

Elite Dome IP Cameras

Day/Night Dome IP Cameras – Vandal Proof Megapixel - H264 Video and Audio



1.4/U/0209/BK

SPECIFICATIONS

Model

BCD752MP

Lan Port / Speed	YES/RJ45 10/100 BaseT + RS-485 interface
Analogue Out	BNC 1.0Vp-p 75ohm
Compression	MPEG4 / dual stream / 32k ~8Mbps (H.264 optional)
Supported Protocols	DDNS, PPPoE, DHCP, SNTP, TCP/IP, ICMP, SMTP, HTTP, RTP, RTSP
Lens / Pixels	2.7 ~ 9mm Varifocal – fixed iris / 2,000,000 max
Frame Rate	12.5fps(1600 × 1200), 25fps(1280 × 720), 25fps(704 × 576), 30fps(704 × 480)
Resolutions	1600x1200,1280x720,800x600,704x576,640x480,528x384,704x288,352x288,176x144
Rotation Angle	Pan:360° Endless. Tilt:0°~90, 3 Axis Gimble
Features	Motion Detection, Mask, Title Overlay
Security	Multiple Level, Password Protected
Management	BiKal EyeSoft, Bundled Software, Internet Explorer, 3G mobiles
Image Sensor	1/3" CMOS / Fixed iris. 0.5 LUX (0.1 Lux Sens Up) @ F1.2
BLC	Auto
Alarm I/O	YES
SD Card	YES
BNC Out	YES
Infra Red	NO
WiFi	NO
Audio	1ch in/out, 3.5mm jack, Ogg Vorbis
Power	12v/24v/POE, 4W
Operating Temp	-10~60°C / IP66 / 80% humidity
Dimension	φ156.5x135.5
Weight	1400g (3.08lbs)
Impact	IEC60068-275Eh,50J;EN50102, exceeding IK10
Supplied With	Fixed Breakout Cable, Free 64ch Surveillance Software

BIKAL NETWORKS LIMITED

4th Floor, 25 Eccleston Square, London, SW1V 1NS, UK

WEB: www.bikal.co.uk EMAIL: uk@bikal.co.uk Tel: [+44 \(0\)844 804 2400](tel:+44208448042400)

Elite Dome IP Cameras

Day/Night Dome IP Cameras – Vandal Proof Megapixel - H264 Video and Audio